



Decorative Wall Panelling



PVC Wall and Ceiling Panelling
Easy Installation
New Designs in 250mm and 1000mm

CADCO PVC panelling provides a smooth, decorative, waterproof wall covering for new and existing interior walls in homes, offices and industrial applications.

Available in a large range of stylish designs and colours

Key features of PVC panels are:

- Fit over existing tiles
- Waterproof and hygienic
- Class 1 fire rated
- Tongue and groove design for quick and easy installation
- Durable - suitable for walls and ceilings
- Lead-free, versatile - for home, office and industrial applications

Available in 250mm x 2600mm and 1000mm x 2400mm panel sizes



Head Office: No. 4 Drumbrughas Ave, Drumbrughas North, Lisnaskea, Co. Fermanagh, N. Ireland, BT92 0QQ
T: 028 (048) 677 22217 F: 028 (048) 677 21713 E: sales@cadconi.com W: www.cadconi.com

Cork: Unit 16 Northpoint Business Park, Mallow Road, Co. Cork

Dublin: Unit 18F Rosemount Park Drive, Rosemount Business Park, Blanchardstown, Dublin 15

250mm Panel Colours


Ceiling Panel with Silver Strip CP02



Marble Grey with Silver Strip CP05



V Groove Grey E4G



Marble Beige MO05



V Groove Beige E5G




White Sparkle RR1



White Ash RR6




Pastel Grey RR7



Pastel Beige RR10 PB



Beige Sparkle RR10



Red Marble RR15



Black Silver Strip Craquelle



Black Sparkle RR2



Black Brushed Silver MO07




Gloss White RR4



1000mm Panel Colours


Pergamon



Rainbow Sparkle



Grey Marble



White Sparkle



Accessories

All trims come in 2.6mtr lengths and available in 3 colours. Internal and external corners in black, white and chrome effect. Start and finish trims in black, white and chrome effect.

Installation

Wall panels are easy to install using a low modulus silicone provided that the surface being covered is smooth and clean. As well as using silicone to fit the panels they can be screwed, nailed and stapled onto wooden support battens.

Due to the limitations of the printing process colours may vary from actual products. Please provide product code when purchasing panels.

Do not expose the panels to direct sunlight or to temperatures above 60°C.